## KW-93 百格刀 Cross-Cut Tester

- \* 二组刀片,刀片的切割宽度为别为1和2毫米; Two sets of cutter, respectively 1mm, 2mm thick.
- \* 刀片由合金钢材料制造, Cutter made of alloy.
- \* 配置了放大镜和毛刷,方便操作。 Provided with magnifer and brush for easy operation.



**KW-LA-26** 



黏油胶纸
Paint Adhension Tape
\* 美国标准 ASTM D 3359-08 指定的用来替代 American
Puma Si P-99 Alternative Tape 的油漆附着力的胶纸;
Paint-adhesion tape as specified by ASTM D 3359-08

\* 规格: 1英寸宽, 66码长, 厚度为0.15毫米; Spec: ne inch wide, 66 yards long, 0.15mm thick.

to substitute American Puma Si P-99 Alternative Tape.

## KW-J-2000 木材水分计 Wood Moisture Content tester

- \* 美国 特荷斯 (Delmhorst)牌木材水分计。 US Brand Delmhorst.
- \* 测量范围: 6%-40%; Measuring range: 6%-40%.
- \* 48种木材设定。 Can set for 48 types of wood.
- \* 内建温度补偿功能;
- Nuilt-in temperature compensating function.

\* 最多可测100个累计读数的平均值; Can calculate average value of maximum 100 accumulated readings.







\* 美国Delelsko公司PosiTector 200B涂层厚度测试仪; Made by Delelsko in US, Positector 200B Coating Thickness Gages.

- \* 无需调校,直接读取涂层厚度数值; No need to adjust or calibrate, read the coating thickness directly.
- \* 双色灯光提示,适用于嘈杂环境使用; Dual indication light, appropriate for use in noisy environment.
- \*具有参数重置功能,随时恢复出厂设置;

Parameter resettable, can recover to original settings anytime as needed.

\*测量范围: 0.5-40µ;

Measuring range: 0.5-40µ