

Specification asse 2. S		Aodularization. Modular design, modular production, modular packing and modular embly. Simple bolted connections can allow for quick and easy assembly within 15 minutes by 2 n-skilled persons from un-pack to pack and power-on.		
Model		KW-PPF-SD-01-WT	KW-PPF-SD-01-BK	
		Mat White	Mat Black	
Spec.	Outer	 Heigth 2260 mm, Width 1066 mm, Depth 1066 mm. Skin-stringer construction design, powder coating. Caster: 4 pcs, 360 degree swivel, Height 50 mm, Load: 200 kg. Feet: 4 pcs, Rubber stand, Height adjustment: 50-80 mm, Load: 200 kg. 		
	Inner	1. Heigth 2130 mm,Width 936 mm,Depth 919 mm. 2. Decorate with PET soundproof cotton, Dotted Grey.		
	Door	 Heigth 2095 mm, Width: 901 mm Glass: 8 mm tempered, with aluminum profile frame. Handle: Stainless Steel 304, Mat Black, 135 degress motion, No-Locking function. Hinge: 3 pcs, Stainless Steel, Mat Black. 		
	Board	1. Height from inner floor 1068 mm,Depth 330 mm,Width 864 mm. 2. MDF board,PVC binding,Mat Black,Rated load: 80 kg		
	Mat	Soft PVC or Nylon carpet		

KW-PPF-SD-01 静音舱 / 电话亭 Phone Booth / Phone Pod

Model		KW-PPF-SD-01-WT	KW-PPF-SD-01-BK
		Mat White	Mat Black
E-parts	Switch	Infrared body sensing switch with adjustable delay of 5-30 seconds	
	Lighting	LED 12W Warm 3500K	
	Charger	2 110VAC socket,1 USB 5 VDC,1 TYPE C 5 VDC	
	Fan	2 fans, Hidden in the roof.	
Package	Overall	Size:2315*1095*530 mm,G.W: 380 kg,N.W: 316 kg	
	Upper	Size: 2310x1086x200 mm, G.W: 127 kg, N.W: 119 kg	
	Middle	Size: 2310x1086x110 mm, G.W: 117 kg, N.W: 112 kg	
	Lower	Size:2310x1086x110 mm,G.W: 88.2 kg,N.W: 78.4 kg	
	Shipment	40 sets per 40"GP	

